

## Post LED Sconce PTS Series

#### **Features**

Modern design featuring a combination of metal and painted finish. Indirect illumination. For use in hallways, corridors, or anywhere general lighting is needed. Vertical or horizontal mounting.

Requires a rectangular 2 in x 4 in. handy box for installation (not included).

#### Construction

Die-cast metal diffuser bracket, stamped metal backplate. Standard mounting holes and hardware are included. Power supply connections must be made inside a handy box (not included).

#### **Finish**

All cast metal components are finished in satin nickel and painted dark grey or white.

#### Diffuser

Clear outer glass diffuser, white inner glass diffuser.

#### **Electrical**

This unit it direct wired with a constant current LED driver rated for 120VAC. Compatible with residential TRIAC and ELV dimming.

#### Lamping

15.5W = 1200 source lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

#### Certification

All fixtures are cULus listed for damp locations. ADA


#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

# LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





### **Ordering Information:**

			Source					
Dark Grey	White	LED	Lumens	CCT	H	W	D	
PTS3151200L30D1SNGY	PTS3151200L30D1SNWH	15.5W	1200	3000K	13-1/2"	3"	3-1/2"	