## PRODUCT DATA SHEET

Product Description: Entry set, ANSI Grade 3. Set includes passage pull with thumb latch, interior right lever. Pull fabricated from die cast zinc with a US15 satin nickel finish. Ships with mounting hardware. Lock ships with mortise latch. Optional drive in latch (product #87396 and #87394) and UL10C fire rated latch (product #87374 and #87373) available. 3" 2 1/4" A I [76 mm] [57 mm] 2 3/8" 2 5/8" [60 mm] [66 mm] 2 3/4" [70 mm] 1 5/8' [41 mm] R1/4" 1" 4 3/16" [R6 mm] [25 mm] [106 mm] 11 15/16" 2 1/2" 1 3/8" [303 mm] [64 mm] 2 5/16' [35 mm] 1 3/4" [59 mm] 5 5/16" 8 5/8"" [44 mm] [135 mm] [219 mm] View From Inside Of The Door ത ത <u>\_</u> C Door Prep: Cross Bore 2 1/8", Edge Bore 1", Mortise Latch Face 1" x 2 1/4", Optional Drive In Latch 1" Diameter Drilled Hole Latches: Ships With Mortise Latch As Shown Above, Optional Drive In Or UL10C Fire Rated Latches Available Backset: Adjustable Latch to 2 3/8" or 2 3/4" **REKEY OPTIONAL** Door Thickness: Fit all 1 3/8" - 1 3/4" Standard Doors Cylinder: Brass with Nickel Plated Brass Keys and 5 Pin Tumbler Kwikset KW1 Keyway ANSÍ 3 KW KEYWAY Strike Plate: 2 1/4" Full Lip Strike Optional (U) Latch Bolt: 1/2" Throw Overall Size: 3" W X 11 15/16" H X 2 1/2" D Material: Die Cast Zinc Finish: US15 Satin Nickel **Cross Reference** Manufacturer Part Number Descriptior **Dakota Entry Set with** Interior Right Lever, KW1, ANSI Grade 3 Part Number:

87366

01/21 04 Sheet 1 of 1

Rev.