# SPECIFICATIONS

#### >> HEADRAIL

Extruded PVC headrail 1.75" width x 1.22" height x 0.06" thick.

### >> HEADRAIL ENDCAPS Injection molded plastic.

#### >> BOTTOMRAIL

Extruded hollow PVC bottomrail 1.18" width x 0.55" height x 0.057" thick.

# >>> BOTTOMRAIL ENDCAPS

Injection molded plastic.



Designer Headrail

#### >> WAND

Extruded PVC Hex shape, Color coordinated, diameter 0.3937"

#### >> SLAT

Extruded PVC .013" to .014" thick x 0.976" width with crown of 0.157."

### >> TILT ROD

Plated steel, 0.138" diameter.

#### >> LADDER

Woven polyester ladder 0.86" spacing.

#### >> TILTER

Injection molded plastic housing.

# >> BOTTOMRAIL ANCHORS

Injection molded plastic.

### >> MOUNTING BRACKET

Plated steel, hidden.

### >> TAPE ROLLER SUPPORT

Injection molded plastic with metal roller minimizing cord fray.



Tilter



Bottomrail of Extruded Hollow PVC

#### >> TAPE ROLLER

Injection molded plastic with ladder locking legs.

### >> INTERNAL CORD

Woven polyester cord 0.035".

# >> HOLD DOWN BRACKET

Injection molded plastic.

#### >> CUSTOMIZATION

22" and below - 0" can be cut off width.

Over 22" - up to 6" total.

No more than 10" may be taken off the length to allow the blind to hold its position.