HARDWOOD

ARBOR PLACE Engineered

Engin







BUILDER + MULTIFAMILY

ARBOR PLACE

HARDWOOD

	US Units	Metric Units
Style Number	SW512	
Construction	Engineered	
Species	Hickory	
Nominal Overall Thickness	3/8"	9.5 mm
Nominal Width	5"	127 mm
Finish	UV Aluminum Oxide	
Gloss Level	20%	
Surface Texture	Scraped	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	37.26 lbs	16.9 kg
SQFT per Carton	29.53 sq ft	2.74 sq m
SQFT per Pallet	1181.2 sq ft	109.73 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

Features

shawfloors.com

An artisan-scraped engineered hickory with sturdy ply core, ArborPlace offers classic scraped styling with a nice balance of uniquetexturing and chatter. The palette of five colors includes on-trendgrey, warm naturals, and a variety of rich browns. And making thisstyle even more appealing is the fact that it's a great value!

Suggested Adhesive

Style Name	Style Number
35MC	HS105
Urebond Plus	SWADH

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.



BUILDER + MULTIFAMILY

ARBOR PLACE

HARDWOOD

Colors





