HARDWOOD

BISCAYNE BAY Engineered







BUILDER + MULTIFAMILY

BISCAYNE BAY

HARDWOOD

	US Units	Metric Units		
Style Number	SW520			
Construction	Engineered			
Species	Birch			
Nominal Overall Thickness	3/8"	9.5 mm		
Nominal Width	5" 127 mm			
Finish	UV Aluminum Oxide			
Gloss Level	20%			
Surface Texture	Scraped			
Edge Description	Micro Bevel			
End Description	Micro Bevel			
Profile	Tongue And Groove			
Weight per Carton	37.79 lbs	17.14 kg		
SQFT per Carton	29.53 sq ft	2.74 sq m		
SQFT per Pallet	1181.2 sq ft 109.73 sq m			
Installation Methods	Nail, Staple, Glue, Floating			
Installation Grade	Above, On, Below			
Variation	Moderate			
GREENGUARD® Certified	Yes			
Cradle-to-Cradle Certified	Yes			
Radiant Heat Approved	Yes			
Residential Warranty	50 Years			
All measurements are nominal.	Cartons may include random lengths.			

Features

shawfloors.com

In this "artisan-crafted" style the scrape combined with gentle chatter, creates a versatile product that has refined, rustic appeal. Subtle birch grain adds to the casual charm, as does the matte finish, which gives a natural, oil-rubbed appearance—a hot designer look! Made with a 6-ply plywood core, planks have micro-beveled ends andedges and come in random lengths—13" to 471/4".

Suggested Adhesive					
Style Name	Style Number				
35MC	HS105				

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.



BUILDER + MULTIFAMILY

BISCAYNE BAY

HARDWOOD

Colors

460 Surfside	493 Bayfront	529 Oceanside	627 Burnside	698 Conway
	A A			
1023 Crescent Beach	2022 Parasail	5034 Windsurf	11071 Seagrass	17051 Low Tide







reference purposes only if printed or downloaded