HARDWOOD

EXPRESSIONS

Engineered





EXPRESSIONS

HARDWOOD

| Style Number SW707 Construction Engineered Species White Oak Nominal Overall Thickness 5/8" 15 mm Nominal Width 7.5" 190.5 mm Finish UV Aluminum Oxide Gloss Level 7% Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | | US Units | Metric Units |
|---|-------------------------------|-------------------------------------|--------------|
| SpeciesWhite OakNominal Overall Thickness5/8"15 mmNominal Width7.5"190.5 mmFinishUV Aluminum OxideGloss Level7%Surface TextureWirebrushedEdge DescriptionMicro BevelEnd DescriptionMicro BevelProfileTongue And GrooveWeight per Carton44.35 lbs20.11 kgSQFT per Carton23.31 sq ft2.16 sq mSQFT per Pallet1165.5 sq ft108.27 sq mInstallation MethodsNail, Staple, Glue, FloatingInstallation GradeAbove, On, BelowVariationExtremely HighGREENGUARD® CertifiedYes | Style Number | SW707 | |
| Nominal Overall Thickness 5/8" 15 mm Nominal Width 7.5" 190.5 mm Finish UV Aluminum Oxide Gloss Level 7% Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified | Construction | Engineered | |
| Nominal Width 7.5" 190.5 mm Finish UV Aluminum Oxide Gloss Level 7% Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified | Species | White Oak | |
| Finish UV Aluminum Oxide Gloss Level 7% Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Nominal Overall Thickness | 5/8" | 15 mm |
| Gloss Level 7% Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Nominal Width | 7.5" | 190.5 mm |
| Surface Texture Wirebrushed Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Finish | UV Aluminum Oxide | |
| Edge Description Micro Bevel End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Gloss Level | 7% | |
| End Description Micro Bevel Profile Tongue And Groove Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Micro Bevel Advisory 108.27 sq m 108.27 sq m 108.27 sq m | Surface Texture | Wirebrushed | |
| ProfileTongue And GrooveWeight per Carton44.35 lbs20.11 kgSQFT per Carton23.31 sq ft2.16 sq mSQFT per Pallet1165.5 sq ft108.27 sq mInstallation MethodsNail, Staple, Glue, FloatingInstallation GradeAbove, On, BelowVariationExtremely HighGREENGUARD® CertifiedYes | Edge Description | Micro Bevel | |
| Weight per Carton 44.35 lbs 20.11 kg SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | End Description | Micro Bevel | |
| SQFT per Carton 23.31 sq ft 2.16 sq m SQFT per Pallet 1165.5 sq ft 108.27 sq m Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Profile | Tongue And Groove | |
| SQFT per Pallet Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | Weight per Carton | 44.35 lbs | 20.11 kg |
| Installation Methods Nail, Staple, Glue, Floating Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | SQFT per Carton | 23.31 sq ft | 2.16 sq m |
| Installation Grade Above, On, Below Variation Extremely High GREENGUARD® Certified Yes | SQFT per Pallet | 1165.5 sq ft | 108.27 sq m |
| Variation Extremely High GREENGUARD® Certified Yes | Installation Methods | Nail, Staple, Glue, Floating | |
| GREENGUARD® Certified Yes | Installation Grade | Above, On, Below | |
| | Variation | Extremely High | |
| Padiant Heat Approved Voc | GREENGUARD® Certified | Yes | |
| Radialit Fleat Applioned fes | Radiant Heat Approved | Yes | |
| Residential Warranty 50 Years | Residential Warranty | 50 Years | |
| All measurements are nominal. Cartons may include random lengths. | All measurements are nominal. | Cartons may include random lengths. | |

Features

Expressions Hardwood features white oak at its best. Part of the Gallery Collection of premium hardwood, Expressions is hand selected by design experts to bring the natural artistry of hardwood into your home. The clean look and understated finishes let the beauty of the wood shine through for a timeless look that ages gracefully.

Suggested Adhesive

| Style Name | Style Number |
|--------------|--------------|
| 35MC | HS105 |
| Urebond Plus | SWADH |

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.



EXPRESSIONS

HARDWOOD

Colors





