

# **RIVERSTONE**

Engineered





### **RIVERSTONE**



	US Units	Metric Units
Style Number	SW593	
Construction	Engineered	
Species	Hickory	
Nominal Overall Thickness	3/8"	8.2 mm
Nominal Width	6.38"	162.05 mm
Finish	ScufResist Platinum	
Gloss Level	20%	
Surface Texture	Heavy Scraped	
Edge Description	Pillowed	
End Description	Pillowed	
Profile	Tongue And Groove	
Weight per Carton	45 lbs	20.41 kg
SQFT per Carton	30.48 sq ft	2.83 sq m
SQFT per Pallet	1371.6 sq ft	127.42 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	Lifetime	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

#### **Features**

Scraped hickory flooring in a low gloss color palette that ranges from cool to warm. The chattered and scraped surface accentuates the naturally wide range of character found in the hickory hardwood species.

#### **Suggested Adhesive**

Style Name	Style Number
35MC	HS105
Urebond Plus	SWADH

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.





## **RIVERSTONE**



### Colors





