


NL-645

Metal Trim with Slot Aperture

TRIM DIMENSIONS



Trim OD: 7-1/4"
Slot Aperture: 1-3/8" x 2-3/4"

FEATURES

Trim

Metal trim with 1-3/8" x 2-1/4" slot aperture that can rotate 135° horizontally. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

Mounting

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

Compatible Housings

Compatible with Low Voltage housings, Low Voltage retrofit kits, and Line Voltage MR16 GU10 retrofit kits.

See individual specification sheets for more information.

Lamp

Low Voltage

20W-50W 12V MR16 (NLIC-601 Series; NL-601 Series; NLR-604 Series)

20W-75W 12V MR16 (NL-601/75 Series; NLR-604/75 Series)

Line Voltage Retrofit Kits

50W 120V MR16 GU10 Max. (NRA-34/10; NRA-37/10)

Low Voltage Retrofit Kits

20W-50W 12V MR16 (NLK-2600; NLK-2600EL)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Metal Trim with Slot Aperture

NL-645: White Metal Trim with Slot Aperture

NL-645B: Black Metal Trim with Slot Aperture

NL-645BZ: Bronze Metal Trim with Slot Aperture

NL-645CO: Copper Metal Trim with Slot Aperture

NL-645N: Natural Metal Trim with Slot Aperture

NORALIGHTING.

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

LOW VOLTAGE

Item Number	Installation Type	Dimensions
NL-601Q	Non-IC New Construction - 120V Magnetic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/277Q	Non-IC New Construction - 277V Magnetic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/1EL	Non-IC New Construction - 120V Electronic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/2EL	Non-IC New Construction - 277V Electronic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/75Q	Non-IC New Construction - 120V Magnetic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/277/75Q	Non-IC New Construction - 277V Magnetic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/75/1EL	Non-IC New Construction - 120V Electronic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NL-601/75/2EL	Non-IC New Construction - 277V Electronic	W: 7-1/2" L: 12-1/2" H: 7-1/2"
NLIC-601QAT	IC Air-Tight New Construction - 120V Mag.	W: 9-1/2" L: 13-1/8" H: 7-3/4"
NLIC-601/1EL	IC Air-Tight New Construction - 120V Elec.	W: 9-1/2" L: 13-1/8" H: 7-3/4"
NLIC-601/2EL	IC Air-Tight New Construction - 277V Elec.	W: 9-1/2" L: 13-1/8" H: 7-3/4"
NLR-604Q	Non-IC Remodel Housing - 120V Magnetic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/277Q	Non-IC Remodel Housing - 277V Magnetic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/1EL	Non-IC Remodel Housing - 120V Electronic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/2EL	Non-IC Remodel Housing - 277V Electronic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/75Q	Non-IC Remodel Housing - 120V Magnetic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/277/75Q	Non-IC Remodel Housing - 277V Magnetic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/75/1EL	Non-IC Remodel Housing - 120V Electronic	W: 6-1/4" L: 14-1/2" H: 7-1/2"
NLR-604/75/2EL	Non-IC Remodel Housing - 277V Electronic	W: 6-1/4" L: 14-1/2" H: 7-1/2"

LINE VOLTAGE RETROFIT KITS

NRA-34/10	Non-IC - Without Lamp	Medium Base Socket adapter
NRA-37/10	Non-IC - With 50W Lamp	Medium Base Socket adapter

LOW VOLTAGE RETROFIT KITS

NLK-2600	Non-IC - 120V Magnetic	W: 4-1/2" L: 4-3/4" H: 5-1/8"
NLK-2600EL	Non-IC - 120V Electronic	W: 5-1/8" L: 5-1/2" H: 4-1/2"

NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040
www.noralighting.com • Specifications subject to change without notice. © 2012
Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com